

Eclipse® EFDX EFDX SERIES



AVAILABLE LENGTHS: 1' - 6'

PRODUCT DESCRIPTION:

The EFDX lighting system is an ultra-low profile, OEM grade lighting product for wet and hot location applications. The EFDX has a variety of mounting methods including integrated magnetics, mechanical fasteners and clips. It has hermetically sealed, submersible lamps, rated IP68 with waterproof connectors.

FEATURES:

- Latest generation of LED components and optics
- Available in 1', 2', 3', 4', 5' and 6' lengths
- All Color Temps available 2700K-5000K (CCT)
- Life rating: 75,000 hrs (L70)
- Lowest thermal heat signature
- Operating Temperatures: -20°C to 80°C (-4°F to 176°F)
- Optional dimming kit available
- Daisy Chain option available

APPLICATIONS:

- Hot Food Bars
- Display Cases
- General Purpose
- Self-Service Bars
- Displays
- Refrigerated Cases
- Beverage Cases
- Covers

COMPLIANCE & SAFETY:



PERFORMANCE AT 4000K:

Model	Length	Watts	Lumens	LPW	CRI
EFDX	13.5"	2.4	318	132	85
EFDX	24.5"	4.8	636	132	85
EFDX	35.5"	7.2	954	132	85
EFDX	46.5"	9.6	1,275	132	85
EFDX	57.5"	12.0	1,600	132	85
EFDX	67.58"	14.4	1,900	132	85



ORDERING GUIDE: Ex: EFDX-4M40-07A-NA-DD12

Model	Size	CRI	CCT(K)	LED	Mount	Lens	Cord	Daisy Chain Cord Length	
EFDX	1	Medium	2700	07A	NA-Magnet	D-Diffused	D-Daisy Chain	02=2"	08=8"
	2	High	3000	14A	NM-End	C-Clear	S-STD 72" Zip Cord	03=3"	09=9"
	3		3500		CM-Clip		F-Female Connector	04=4"	10=10"
	4		4000		TM-Tape			05=5"	11=11"
	5		5000					06=6"	12=12"
	6							07=7"	