



Catalog#: \_\_\_\_\_  
 Type: \_\_\_\_\_  
 Date: \_\_\_\_\_  
 Project: \_\_\_\_\_  
 Prepared By: \_\_\_\_\_  
 Comments: \_\_\_\_\_

**Solar Eclipse®**  
**SELS SERIES**  
**HIGH OUTPUT**



**ULTRA LOW PROFILE**



**AVAILABLE LENGTHS: 1' - 6'**



**PRODUCT DESCRIPTION:**

The SELS High Output lighting system is an energy efficient and an easily controllable solution to the conventional T8 & T12 systems used in vertical cooler/freezer applications. The product's long life and lower wattages reduce the additional maintenance costs and the lower wattage can help reduce the overall compressor load.

**FEATURES:**

- Distributes light evenly over the product shelves
- Available in 1', 2', 3', 4', 5' and 6' lengths
- Class 2 external power supply 120 - 277 VAC
- All Color Temps available 2700K-5000K (CCT)
- Life rating: 75,000 hrs (L70)
- Lowest thermal heat signature
- Greatly reduced total life cycle costs
- Optional dimming kit available

**APPLICATIONS:**

- Vertical Display Cases
- Refrigerated Cases
- Beverage Cases
- Freezer Cases

**COMPLIANCE & SAFETY:**



**PERFORMANCE AT 4000K:**

Model	Watts	Lumens	CRI	Length	Width	Depth
SELS-4C	28.8	2,460	80+	45.7"	2.80"	.85"
SELS-4L & 4R	14.4	1,240	80+	45.7"	1.81"	.85"
SELS-5C	36.0	3,080	80+	56.3"	2.80"	.85"
SELS-5L & 5R	18.0	1,540	80+	56.3"	1.81"	.85"
SELS-6C	43.2	3,700	80+	66.9"	2.80"	.85"
SELS-6L & 6R	21.6	1,860	80+	66.9"	1.81"	.85"

**ORDERING GUIDE: Ex: SELS-5C40-EM14A**

Model	Length	CCT(K)
SELS-4C	4' Center	27 = 2700
SELS-4L & 4R	4' Left & Right	30 = 3000
SELS-5C	5' Center	35 = 3500
SELS-5L & 5R	5' Left & Right	40 = 4000
SELS-6C	6' Center	50 = 5000
SELS-6L & 6R	6' Left & Right	

