



Catalog#: _____
Type: _____
Date: _____
Project: _____
Prepared By: _____
Comments: _____

Eclipse® EFDX

EFDX SERIES



AVAILABLE LENGTHS: 1' - 6'

PRODUCT DESCRIPTION:

The EFDX lighting system is an ultra-low profile, OEM grade lighting product for wet and hot location applications. The EFDX has a variety of mounting methods including integrated magnetics, mechanical fasteners and clips. It has hermetically sealed, submersible lamps, rated IP68 with waterproof connectors.

FEATURES:

- Latest generation of LED components and optics
- Available in 1', 2', 3', 4', 5' and 6' lengths
- All Color Temps available 2700K-5000K (CCT)
- Life rating: 75,000 hrs (L70)
- Lowest thermal heat signature
- Operating Temperature of -20°C to 50°C (-4°F to 122°F)
- Customized sizes available
- Wet location rated

APPLICATIONS:

- Hot Food Bars
- Display Cases
- General Purpose
- Self-Service Bars
- Displays
- Refrigerated Cases
- Beverage Cases
- Coves

COMPLIANCE & SAFETY:



PERFORMANCE AT 4000K:

Model	Length	Watts	Lumens	LPW	CRI
EFDX-1	11.63"	3.6	567	157.5	85
EFDX-2	23.85"	7.2	1,134	157.5	85
EFDX-3	33.63"	10.8	1,701	157.5	85
EFDX-4	45.96"	14.4	2,268	157.5	85
EFDX-5	55.78"	18.0	2,835	157.5	85
EFDX-6	68.01"	21.6	3,402	157.5	85



ORDERING GUIDE: Ex: EFDX-4M40-36C-NA-DD12

Model	Size	CRI	CCT(K)	LED	mA	Mount	Lens	Cord	Daisy Chain Cord	
EFDX	1	Medium	2700	36A	15	NA-Magnet	D-Diffused	D-Daisy Chain	02=2"	08=8"
	2	High	3000	36B	20	NM-End	C-Clear	S-STD 72" Zip Cord	03=3"	09=9"
	3		3500	36C	26	CM-Clip		F-Female Connector	04=4"	10=10"
	4		4000			TM-Tape			05=5"	11=11"
	5		5000						06=6"	12=12"
	6								07=7"	

